

PART #	COLOR	S	CREWS			REVISIONS	i	
CH090-4D-BK	BLACK		SCREWS - MATERIAL: 410 SERIES SS		ECR/DCR REV.	DESCRIPTION INITIAL RELEASE	DA 12-1	TE APPD 3-13 -
		· · ·			DCR-0275 1	REVISED SD SCREW MATERIAL FRO	204.40.0.00	3-14 CGS
					- 2	TO 400 SERIES SS UPDATED TABLE		1-24 DDC
.88	.75	J						
		3.63				, .50	20	
		1.08	<b>PACKAGING INSTRUCTIONS</b> POLYBAG CONTAINING: - (2) HINGES - (1) ADJUSTMENT WRENCH - (1) INSTRUCTION SHEET - (1) WARRANTY SHEET - (1) POLYBAGGED SCREW PACK (S.	EE TABLE)	DIMENSIONS ARE TOLERANCES: FRACTIONAL (1/) ANGULAS: MACI TWO PLACE DEC THREE FLACE DEC PROPRIETARY AND THE INFORMATION O DRAWING IS THE 32 NATIONWIDE IND REPRODUCTION IN PA WITHOUT THE WRITE NATIONWIDE INDUST	6' NATT   11' BEND 21' IND   INAL 20.01 IND   INAL 20.05 ORNAME   CONFIDENTIAL ORNAME   CMTAINED IN THIS RE PROPERTY OF USIRES. ANY SIZE   SIZE DWGS. NO.	IONWIDI USTRIES ENTAL PLAS LOSING HIN CSCH090	® STIC IGE


PART #	COLOR	
KLTRV-250-BK	BLACK	


## PACKAGING INSTRUCTIONS


- POLYBAG CONTAINING:
- (1) LATCH ASSEMBLY
- (1) KEEPER ASSEMBLY
- (1) INSTRUCTION SHEET
- (1) WARRANTY SHEET
- POLYBAG CONTAINING:
  - (4) #8 X 1" PAN HD PHILLIPS SD SCREWS MATERIAL: 410 SS
  - (5) #8 X 1" FLAT HD PHILLIPS SD SCREWS MATERIAL: 410 SS











DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/16" ANGULAR: MACH_1 BEND_11" TWO PLACE DECIMAL ±0.01 THREE PLACE DECIMAL ±0.005 <b>PROPRIETARY AND CONFIDENTIAL</b> THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF	NATIONWIDE INDUSTRIES® KEYSTONE® TRAVERSE 2-SIDED LOCKING LATCH 2.5"	
NATIONWIDE INDUSTRIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NATIONWIDE INDUSTRIES IS PROHIBITED.	SIZE DWG. CSKLTRV-250 SCALE:13 WEIGHT: SHEET 1 OF	REV. -